



# SAFECO BRAND GFCX-NPT

2" 125# ANSI FEMALE THREADED  
DUCTILE CAST IRON NATURAL GAS FILTER

## FILTER ELEMENT

Number of Elements : One

Inner Shield : 22 Ga. CS Perforated  
Outer Shield : 18 Ga. CS Perforated  
End Caps : 22 Ga CS EP  
MIN Collapse : 25 PSID

Cellulose Part # : 020040110-10C  
Retention : 10 Microns @ 99%

Polyester Part # : 020040110-5P  
Retention : 5 Microns @ 99%

## CONSTRUCTION MATERIALS

Closure Type : Bolted  
Davit Arm : None, Handle  
Closure Bolts : Grade 8 Hex, Zinc Plated  
Closure Cap : A-536 Gr 65-45-12  
Gasket Size : O-Ring, 357  
Gasket Mat'l : BUNA  
Closure Hub : A-536 Gr 65-45-12  
Body : A-536 Gr 65-45-12  
Bottom : A-536 Gr 65-45-12  
Inlet : A-536 Gr 65-45-12  
Outlet : A-536 Gr 65-45-12  
Drain : A-536 Gr 65-45-12  
High-side DP Tap : A-536 Gr 65-45-12  
Low-side DP Tap : N / A  
Leg Supports : N / A  
Skirt : N / A  
Base Plate : N / A  
Net Weight : 43 lbs

## SCHEDULE OF OPENINGS

Inlet : 2" F-NPT  
Outlet : 2" F-NPT  
Drain : 1/2" F-NPT, w/ Plug  
Vent : 1/4" F-NPT, w/ Plug  
High-side DP Tap : 1/4" F-NPT, w/ Plug  
Low-side DP Tap : N/A

## DESIGN

Pressure Class : ASME / ANSI 125  
Max Pressure : 180 psig  
Max Temperature : 100 Degrees F  
Corrosion Allowance : None  
CODE Stamped : N / A

## TESTING

Hydrostatic Test : 375 PSIG  
Pneumatic Test : 80 PSIG  
Radiography : N / A

## COATING

2 mils Oxidating Primer,  
Sand Blasting and  
Other Coatings Available

