



SAFECO BRAND GFC-FF

2" 125# ANSI FLAT-FACED
DUCTILE CAST IRON NATURAL GAS FILTER

FILTER ELEMENT

Number of Elements : One

Inner Shield : 22 Ga. CS Perforated

Outer Shield : 18 Ga. CS Perforated

End Caps : 22 Ga CS EP

MIN Collapse : 25 PSID

Cellulose Part # : 020040080-10C

Retention : 10 Microns @ 99%

Polyester Part # : 020040080-5P

Retention : 5 Microns @ 99%

CONSTRUCTION MATERIALS

Closure Type : Bolted

Davit Arm : None, Handle

Closure Bolts : Grade 8 Hex, Zinc Plated

Closure Cap : A-536 Gr 65-45-12

Gasket Size : O-Ring, 357

Gasket Mat'l : BUNA

Closure Hub : A-536 Gr 65-45-12

Body : A-536 Gr 65-45-12

Bottom : A-536 Gr 65-45-12

Inlet : A-536 Gr 65-45-12

Outlet : A-536 Gr 65-45-12

Drain : A-536 Gr 65-45-12

High-side DP Tap : A-536 Gr 65-45-12

Low-side DP Tap : A-536 Gr 65-45-12

Leg Supports : N / A

Skirt : N / A

Base Plate : N / A

Net Weight : 43 lbs

SCHEDULE OF OPENINGS

Inlet : 2" 125# ANSI

Outlet : 2" 125# ANSI

Drain : 1/2" F-NPT, w/ Plug

Vent : 1/4" F-NPT, w/ Plug

High-side DP Tap : 1/4" F-NPT, w/ Plug

Low-side DP Tap : 1/4" F-NPT, w/ Plug

DESIGN

Pressure Class : ASME / ANSI 125

Max Pressure : 180 psig

Max Temperature : 100 Degrees F

Corrosion Allowance : None

CODE Stamped : N / A

TESTING

Hydrostatic Test : 375 PSIG

Pneumatic Test : 80 PSIG

Radiography : N / A

COATING

2 mils Oxidating Primer,

Sand Blasting and

Other Coatings Available

