

# SAFECO BRAND GFT-02-300

2" 300# ANSI RAISED-FACE  
FABRICATED STEEL NATURAL GAS FILTER



## FILTER ELEMENT

Number of Elements : One

Inner Shield : 22 Ga. CS Perforated  
Outer Shield : 18 Ga. CS Perforated  
End Caps : 22 Ga CS EP  
MIN Collapse : 25 PSID

Cellulose Part # : 020040170-10C  
Retention : 10 Microns @ 99%

Polyester Part # : 020040170-5P  
Retention : 5 Microns @ 99%

## CONSTRUCTION MATERIALS

Closure Type : Bolted  
Davit Arm : None, Handle  
Closure Bolts : SA-193 GR B-7  
Closure Cap : SA-105  
Gasket Size : 6" 300# RING  
Gasket Mat'l : NON-ASBESTOS  
Closure Hub : SA-105  
Body : SA-106 GR B  
Bottom : SA-234 GR WPB  
Inlet : SA-105 / SA-106 GR B  
Outlet : SA-105 / SA-106 GR B  
Drain : SA-105  
High-side DP Tap : SA-105  
Low-side DP Tap : SA-105  
Leg Supports : N / A  
Skirt : N / A  
Base Plate : N / A  
Net Weight : 170 lbs

## SCHEDULE OF OPENINGS

Inlet : 2" 300# ANSI RF  
Outlet : 2" 300# ANSI RF  
Drain : 1/2" F-NPT, w/ Plug  
Vent : 1/4" F-NPT, w/ Plug  
High-side DP Tap : 1/4" F-NPT, w/ Plug  
Low-side DP Tap : 1/4" F-NPT, w/ Plug

## DESIGN

Pressure Class : ASME / ANSI 300  
Max Pressure : 740 psig  
Max Temperature : 100 Degrees F  
Corrosion Allowance : None  
CODE Stamped : Available

## TESTING

Hydrostatic Test : 1125 PSIG  
Pneumatic Test : 80 PSIG  
Radiography : Available RT-1

## COATING

2 mils Oxidating Primer,  
Sand Blasting and  
Other Coatings Available

